

Lpg volume correction factor table Reference

lpg volume correction factor table: An Essential Guide to Understanding and Using Volume Correction Factors for LPG

In the LPG industry, accurate measurement of gas volume is vital for ensuring fair trade, billing, and safety. However, LPG (liquefied petroleum gas) volume can vary significantly depending on temperature, pressure, and other environmental conditions. To address these variations, a LPG volume correction factor table is used to standardize measurements, allowing consistent and accurate volume calculations regardless of measurement conditions. This comprehensive guide explores the concept of volume correction factors, how to interpret a correction factor table, and practical applications to ensure precision in LPG handling.

What is an LPG Volume Correction Factor?

An LPG volume correction factor (VCF) is a numerical value used to adjust the measured volume of LPG to a standard reference condition, typically at 20°C (68°F) and atmospheric pressure. Because LPG expands or contracts with temperature and pressure changes, directly measuring the volume without correction can lead to inaccuracies.

Why Use a Volume Correction Factor?

- Standardization: Converts all measurements to a common basis for comparison.
- Fair Billing: Ensures consumers are billed accurately based on standardized volumes.
- Safety: Maintains accurate records for safety inspections and regulatory compliance.
- Inventory Management: Facilitates precise tracking of LPG quantities.

Understanding the Components of the Volume Correction Factor Table

A typical LPG volume correction factor table contains multiple columns, each representing essential parameters:

Key Parameters in the Table

- Temperature (°C or °F): The ambient temperature at which measurement occurs.
- Pressure (kPa or psi): The pressure during measurement.
- Correction Factor (VCF): The numerical factor applied to the measured volume to obtain the

standard volume.

Additional Data Often Included

- Density of LPG: Useful for conversions between volume and mass.
- Specific Gravity: For understanding LPG's relative density compared to water.
- Conversion Factors: For transitioning between units (e.g., liters to gallons).

How to Read and Use a Volume Correction Factor Table

Step 1: Measure the LPG Volume

Use appropriate equipment (e.g., calibrated tanks, meters) to measure the LPG volume at the current temperature and pressure.

Step 2: Record Measurement Conditions

Note the exact temperature and pressure during measurement, as these directly influence the correction factor.

Step 3: Locate Corresponding Values in the Table

Find the row that matches or closely approximates the measured temperature and pressure.

Step 4: Apply the Correction Factor

Multiply the measured volume by the correction factor:

...

Standard Volume = Measured Volume × Correction Factor (VCF)

...

Example Calculation

Suppose:

- Measured LPG volume: 1000 liters

- Temperature: 30°C
- Pressure: 100 kPa

From the correction factor table, the VCF for these conditions is 0.98.

Calculation:

...

Standard Volume = 1000 liters $\times$ 0.98 = 980 liters

...

This adjusted volume reflects the volume at standard conditions.

Types of Volume Correction Factors

Different tables and standards may use various correction factors based on measurement practices:

- ISO 6976 Correction Factors

Based on the ISO 6976 standard, these factors account for temperature and pressure variations specific to LPG.

- API (American Petroleum Institute) Correction Factors

Used predominantly in the US, these factors follow API standards for petroleum products.

- Regional or Company-Specific Tables

Some companies develop their correction factors tailored to their equipment and operational conditions.

Factors Affecting LPG Volume and Correction

Understanding what influences LPG volume helps in selecting the right correction factor:

Temperature

- LPG expands at higher temperatures.
- Correction factors usually decrease as temperature increases because the gas volume at standard conditions is less than the measured volume.

Pressure

- Increased pressure compresses LPG, reducing volume.
- Correction factors adjust for pressure deviations from atmospheric pressure.

Density and Composition

- Variations in LPG composition affect density and volume.
- Some correction tables include specific factors based on LPG grades.

Practical Applications of LPG Volume Correction Factors

- Billing and Commercial Transactions

Accurate correction ensures fair pricing based on standardized volume measurements.

- Inventory Management

Refining inventory records by correcting measured volumes helps prevent losses and discrepancies.

- Regulatory Compliance

Meet legal and safety standards requiring volume corrections as part of reporting.

- Quality Control and Safety Checks

Ensures LPG storage and transfer are monitored accurately for safety compliance.

Developing and Maintaining a Volume Correction Factor Table

Steps to Create a Custom Correction Table

- Gather Data: Record LPG volume measurements across a range of temperatures and pressures.
- Analyze Data: Use statistical methods to derive correction factors.
- Validate: Cross-check with industry standards or calibration experiments.
- Update Regularly: Adjust the table as equipment and conditions evolve.

Best Practices

- Use calibrated equipment for measurements.
- Maintain detailed records of environmental conditions.
- Train personnel in proper measurement and correction procedures.
- Cross-reference with recognized standards like ISO 6976 or API guidelines.

Importance of Standardized Correction Factors in the LPG Industry

Adopting standardized correction factors and tables is crucial for:

- Transparency: Building trust between suppliers and consumers.
- Accuracy: Ensuring measurements reflect true LPG quantities.
- Compliance: Meeting legal and safety regulations.
- Efficiency: Streamlining operations through consistent measurement practices.

Conclusion

A lpg volume correction factor table is an indispensable tool for anyone involved in the measurement, sale, or management of LPG. By understanding how temperature, pressure, and other conditions influence LPG volume, industry professionals can accurately convert measured volumes to standard conditions. This not only promotes fair trade and precise inventory control but also ensures safety and regulatory compliance. Developing, maintaining, and correctly applying correction factor tables empower stakeholders to operate efficiently and transparently in the dynamic LPG market.

FAQs

Q1: Why is it necessary to correct LPG volume measurements?

Because LPG volume varies with temperature and pressure, corrections ensure measurements reflect the true volume at standard conditions, enabling fair transactions and accurate inventory management.

Q2: How often should I update my volume correction factor table?

Regular updates are recommended whenever there are changes in measurement equipment, environmental conditions, or industry standards. Typically, quarterly or annually is advisable.

Q3: Can I use a generic correction factor table for all LPG types?

Not always. Different LPG compositions can influence correction factors. It's best to use or develop correction tables tailored to your specific LPG grades and operational conditions.

Q4: Are correction factors standardized internationally?

Standards like ISO 6976 and API provide internationally recognized correction methods, but specific correction factors may vary regionally or based on company practices.

By understanding and properly utilizing a lpg volume correction factor table, stakeholders can ensure accurate, fair, and safe LPG transactions and management.

LPG Volume Correction Factor Table: A Comprehensive Guide to Accurate Measurement and Usage

In the world of liquefied petroleum gas (LPG), precise measurement is essential for both consumers and suppliers to ensure fair transactions, accurate billing, and safe handling. One of the fundamental tools used in achieving this accuracy is the LPG volume correction factor table. This table is a vital reference that allows users to convert the measured volume of LPG at a given temperature and pressure to a standardized volume, typically at a reference temperature and pressure. Understanding how to interpret and apply the LPG volume correction factor table is crucial for professionals in the industry, regulators, and even end-users who want to grasp the nuances of LPG measurement.

What is an LPG Volume Correction Factor?

The LPG volume correction factor (VCF) is a numerical value used to adjust the volume of LPG measured under varying temperature and pressure conditions to a standard reference condition. Since gases expand or contract based on temperature and pressure, the raw volume readings taken from tanks or meters are not directly comparable unless corrected. The correction factor accounts for these variations, ensuring that volume measurements reflect consistent and standardized conditions.

Why Is the LPG Volume Correction Factor Important?

- Fair Billing: Accurate measurement ensures consumers are billed correctly based on the true volume of LPG they receive.
- Quality Control: Suppliers can verify the amount of LPG supplied or stored, aligning with regulatory standards.
- Safety: Proper measurement helps in assessing the amount of LPG present, preventing over-pressurization and leaks.
- Inventory Management: Companies can maintain precise records of LPG stocks, reducing losses and improving operational efficiency.

The Fundamentals of LPG Volume Measurement

Before delving into the correction factors, it's essential to understand the basic principles:

- Standard Conditions: Typically, LPG volume is standardized at 15°C (59°F) and 1 atmosphere pressure (101.3 kPa).
- Actual Conditions: The temperature and pressure at which LPG is measured in tanks or meters vary, influencing the volume.
- Measurement Devices: Devices like volumetric tanks, flow meters, or dip sticks are used to measure the physical volume.

Understanding the LPG Volume Correction Factor Table

The LPG volume correction factor table provides a set of values that correspond to various temperatures and pressures. These tables are constructed based on the gas's physical properties and the gas laws (Boyle's Law, Charles's Law, etc.).

Key components of the table include:

- Temperature Range: Usually from -20°C up to 40°C or higher, depending on regional standards.
- Pressure Range: From atmospheric pressure up to several bar, as per storage and transportation conditions.
- Correction Factors: Numerical values indicating how much to multiply the measured volume to obtain the standard volume.

How to Use the LPG Volume Correction Factor Table

Applying the correction factor involves a straightforward process:

- Measure the LPG volume at the current temperature and pressure.
- Identify the correction factor from the table corresponding to the measured temperature and pressure.
- Multiply the measured volume by the correction factor to find the volume at standard conditions.

Formula:

$$\text{Standard Volume} = \text{Measured Volume} \times \text{Correction Factor}$$

Step-by-Step Guide to Reading and Applying the Table

- Collect Accurate Measurements
 - Use calibrated instruments to determine the current temperature and pressure of LPG.
 - Measure the volume of LPG in the tank or pipeline accurately.
- Find the Corresponding Correction Factor
 - Locate the row in the table that matches the measured temperature.
 - Find the column that corresponds to the measured pressure.
 - Cross-reference to find the correction factor value.
- Calculate the Corrected Volume
 - Multiply the raw volume measurement by the correction factor.
 - The result is the volume adjusted to standard conditions.

Example:

Suppose you measured 1,000 liters of LPG at 25°C and 1.2 bar.

- From the table, at 25°C and 1.2 bar, the correction factor might be 0.98.
- Corrected volume = 1,000 liters $\times$ 0.98 = 980 liters (standard volume).

Factors Affecting LPG Volume Correction Factors

The correction factors are influenced by:

- Temperature Variations: LPG expands when heated; correction factors decrease with rising temperature.
- Pressure Variations: Increased pressure compresses LPG, requiring adjustment.
- Gas Composition: Different LPG blends may have slight variations affecting the correction factors.

Regional Standards and Variations

Different countries and organizations may adopt varying standards for correction tables. For example:

- ISO Standards: International guidelines provide typical correction factors.
- Regional Regulations: Local standards may specify particular correction conditions and values.
- Industry Practice: Some industries may adopt proprietary correction tables tailored to specific equipment or conditions.

Practical Applications of the LPG Volume Correction Factor Table

- Fuel Stations: Ensuring customers pay for the correct volume of LPG dispensed.
- Transport and Storage: Adjusting measured volumes during transportation to account for temperature fluctuations.
- Sales and Billing: Generating accurate invoices based on corrected volume measurements.
- Inventory Audits: Verifying stored LPG quantities against recorded data.
- Regulatory Compliance: Meeting legal standards for measurement accuracy.

Tips for Accurate Use of the LPG Volume Correction Table

- Always measure temperature and pressure precisely at the point of volume measurement.
- Use calibrated instruments for temperature and pressure readings.
- Consult the latest correction tables relevant to your region and industry standards.
- When in doubt, seek professional calibration and verification services.
- Maintain a record of correction factors used for audit and compliance purposes.

Conclusion

The LPG volume correction factor table is an indispensable tool for ensuring measurement accuracy and fairness in LPG transactions. By understanding how to interpret and apply correction factors, industry professionals can improve operational efficiency, uphold safety standards, and maintain regulatory compliance. Whether you are managing storage tanks, dispensing LPG at a filling station, or conducting audits, mastering the use of volume correction factors ensures that everyone in the LPG supply chain operates with precision and integrity. Proper application of these correction factors ultimately benefits consumers, suppliers, and regulators alike, fostering trust and transparency in the LPG industry.

Question What is an LPG volume correction factor table? An LPG volume correction factor table is a reference tool used to adjust the measured volume of LPG to a standard temperature, accounting for temperature variations that affect LPG density and volume. **Why is it important to use a volume correction factor table for LPG?** Using a volume correction factor table ensures accurate measurement of LPG volume by compensating for temperature differences, which is essential for fair billing, inventory management, and safety compliance. **How do I read and interpret an LPG volume correction factor table?** To interpret the table, locate your measured LPG temperature and volume, then apply the corresponding correction factor to obtain the standardized volume at the reference temperature, typically 15°C or 20°C. **What are the standard reference temperatures used in LPG volume correction tables?** The most common reference temperatures are 15°C and 20°C, as these are standard conditions for volume measurement and comparison in the LPG industry. **Can I use an LPG volume correction factor table for different types of LPG (propane, butane)?** Yes, but it is important to use the appropriate correction factor table specific to the type of LPG, as propane and butane have different physical properties and correction factors. **How often should I update or verify the LPG volume correction factors in the table?** Correction factors should be verified regularly, especially when there are changes in LPG properties or measurement standards, and typically updated annually or as recommended by industry regulations. **Are there digital tools or software available for calculating LPG volume correction factors?** Yes, several software solutions and mobile apps are available that automate the calculation of LPG volume correction factors, making it easier and more accurate for industry professionals to perform measurements.

Related keywords: LPG volume correction factor, LPG correction table, LPG temperature correction, LPG pressure correction, LPG volume calculation, LPG density table, LPG measurement standards, LPG calibration factor, LPG conversion chart, LPG volume correction chart

electric load factor formula

electric load factor formula: A Comprehensive Guide to Understanding and Calculating Load Factors

Understanding the concept of load factors is essential for electrical engineers, power plant operators, and energy consumers aiming to optimize energy usage and improve system efficiency. The electric load factor formula provides a quantitative measure of how effectively electrical energy is utilized over a specific period. This article explores the electric load factor formula in depth, explaining its significance, how to calculate it, and its applications in real-world scenarios.

What Is the Electric Load Factor?

The electric load factor is a dimensionless ratio that indicates the efficiency of electrical energy consumption over a given time frame. It reflects the degree to which the maximum demand (peak load) is utilized relative to the total energy consumed.

Definition of Load Factor

The load factor is defined as the ratio of the average load (or demand) over a period to the maximum load during that same period. A higher load factor signifies that the energy is being used more uniformly, leading to better system utilization and reduced operational costs.

Importance of the Load Factor

- Operational Efficiency: Helps utilities optimize generation and distribution.
- Cost Savings: Higher load factors reduce per-unit costs.
- System Planning: Aids in designing infrastructure capable of handling peak loads efficiently.
- Energy Management: Assists consumers in understanding their usage patterns.

Electric Load Factor Formula

The fundamental formula to compute the electric load factor is:

$$\text{Load Factor (LF)} = (\text{Average Load}) / (\text{Maximum Load})$$

Where:

- Average Load is the total energy consumed divided by the period length.
- Maximum Load is the peak demand during that period.

This ratio is often expressed as a decimal or percentage:

- Decimal form: e.g., 0.75
- Percentage form: e.g., 75%

Expressing the Formula in Terms of Energy and Peak Demand

For practical calculations, the formula can be written as:

$$LF = (\text{Total Energy Consumed in a Period}) / (\text{Maximum Demand} \times \text{Time Period})$$

Where:

- Total energy is usually measured in kilowatt-hours (kWh).
- Maximum demand is measured in kilowatts (kW).
- Time period is measured in hours (h).

Note: Always ensure units are consistent when applying the formula.

Calculating the Electric Load Factor: Step-by-Step

To calculate the load factor effectively, follow these steps:

- **Determine the Total Energy Consumption:** Obtain the total energy consumed over the period (e.g., daily, monthly, yearly). This data is often recorded by energy meters.
- **Identify the Peak Demand:** Find the maximum load recorded during the period. This can be the highest demand recorded in the energy meter logs or demand readings.
- **Measure the Time Period:** Decide the period over which calculations are to be made (e.g., 24 hours, 30 days).
- **Calculate the Average Load:** Divide the total energy consumed by the total time period:

$$\text{Average Load} = \text{Total Energy Consumed} / \text{Total Time Period}$$

- **Apply the Load Factor Formula:** Substitute the values into the load factor formula:

$$LF = \text{Average Load} / \text{Maximum Load}$$

Example Calculation

Suppose a factory consumes 720,000 kWh in a month (30 days), and the maximum demand recorded during that month is 2,400 kW.

- Total energy consumed = 720,000 kWh
- Time period = 30 days × 24 hours/day = 720 hours
- Average load = 720,000 kWh / 720 hours = 1,000 kW

Applying the formula:

$$LF = 1,000 \text{ kW} / 2,400 \text{ kW} = 0.4167 \text{ or } 41.67\%$$

This indicates that, on average, the factory operates at about 41.67% of its maximum demand, reflecting a moderate load factor.

Factors Influencing the Electric Load Factor

Several factors impact the load factor of a system or consumer:

- **Demand Patterns:** Consistent demand leads to higher load factors.
- **Operational Hours:** Extended operational hours can improve load factor.
- **Type of Consumer:** Industrial users often have higher load factors compared to residential consumers.
- **Energy Efficiency Measures:** Implementation of energy-saving technologies can influence overall load patterns.

Applications of Electric Load Factor

Understanding and calculating the load factor has numerous applications:

1. Utility Load Management

Utilities use load factor data to optimize generation schedules, reduce peak load demands, and plan capacity expansions.

2. Cost Optimization

Consumers with high load factors typically pay lower per-unit charges since they utilize energy more

efficiently.

3. Power Plant Design and Operation

Designing power plants with an understanding of expected load factors ensures optimal capacity utilization.

4. Energy Policy and Planning

Government agencies and policymakers analyze load factors to develop sustainable energy strategies.

Limitations and Considerations

While the electric load factor is a valuable metric, it has limitations:

- It does not provide information about the variability of load within the period.
- High load factor does not necessarily mean efficient energy use if total consumption is high.
- It is a historical measure and may not predict future demand patterns accurately.

Therefore, it should be used in conjunction with other metrics like peak demand, load profile, and capacity factor for comprehensive analysis.

Conclusion

The electric load factor formula is a fundamental tool for assessing the efficiency of electrical energy usage over a period. By understanding how to calculate and interpret load factors, utilities, industries, and consumers can make informed decisions to optimize energy consumption, improve system reliability, and reduce costs. Mastery of the load factor concept and its calculation is essential for effective energy management and sustainable power system operations.

Whether you're a professional in the energy sector or a curious consumer, appreciating the significance of the load factor and how it is derived empowers you to better understand the dynamics of electrical systems and their impact on efficiency and cost.

Understanding the Electric Load Factor Formula: A Comprehensive Guide

In the realm of electrical engineering and energy management, the electric load factor formula plays a pivotal role in assessing the efficiency and utilization of electrical power systems. Whether you're an engineer, energy analyst, or facility manager, grasping how to calculate and interpret load factors

can lead to more effective energy consumption strategies and cost savings. This article offers an in-depth exploration of the electric load factor formula, its significance, how to compute it, and practical applications.

What Is the Electric Load Factor?

Before diving into the formula, it's essential to understand the concept of load factor itself. The electric load factor measures the efficiency with which electrical energy is used over a specific period. It compares the average load to the maximum load, providing insight into how consistently electricity is consumed.

Definition:

The electric load factor is a ratio that indicates the portion of the maximum demand that is actually used over a given period, typically a year, month, or day.

Why It Matters:

- It helps utilities and consumers identify opportunities for energy efficiency.
- A higher load factor signifies more consistent and efficient use of power.
- It influences the sizing of generation and distribution infrastructure.

The Electric Load Factor Formula

The electric load factor formula is straightforward but powerful. It mathematically expresses the relationship between the average load and the maximum load during a specific period.

Formula:

Load Factor (LF) = (Average Load) / (Maximum Load)

Expressed as a percentage:

LF (%) = [(Average Load) / (Peak Load)] × 100

Where:

- Average Load is the total energy consumed over the period divided by the number of hours in that period.

- Maximum Load (or peak demand) is the highest level of power demand recorded during the period.

Calculating the Electric Load Factor: Step-by-Step

To accurately compute the electric load factor, follow these steps:

- Determine Total Energy Consumption
 - Gather energy consumption data over your chosen period (day, month, year).
 - Usually expressed in kilowatt-hours (kWh).
 - Example: If a facility consumes 300,000 kWh in a month.
- Calculate the Total Number of Hours
 - Decide the period length and note the number of hours in that period.
 - For example, a month typically has 30 days × 24 hours = 720 hours.
- Compute the Average Load
- Use the formula:

Average Load (kW) = Total Energy Consumption (kWh) / Total Hours (h)

- Example:

Average Load = 300,000 kWh / 720 h = 416.67 kW

- Identify the Peak Demand

- Obtain the highest recorded demand during the period, usually from utility billing data or energy monitoring systems.

- Example: The maximum demand recorded is 600 kW.

- Apply the Load Factor Formula

- Plug the numbers into the formula:

$$LF = (\text{Average Load}) / (\text{Maximum Load})$$

- $LF = 416.67 \text{ kW} / 600 \text{ kW} = 0.694$ or 69.4%

- Interpret the Result

- A load factor of 69.4% indicates that, on average, the facility uses about 69.4% of its peak demand throughout the period.

- This suggests relatively steady and efficient energy usage.

Practical Applications of the Electric Load Factor

Understanding and calculating the electric load factor has significant implications across various sectors:

Energy Efficiency and Cost Management

- Identify Underutilized Capacity: A low load factor suggests the system is not being used efficiently, prompting measures to improve load management.

- Optimize Infrastructure Sizing: Utilities can better design generation and distribution systems by understanding load patterns.

- Reduce Energy Costs: Facilities can implement demand management strategies during peak periods to lower bills.

Power Generation Planning

- Power plants rely on load factor data to determine the most efficient operation schedules.

- High load factors indicate a consistent demand, enabling more economical operation.

Environmental Impact

- Improved load factors lead to more efficient energy use, reducing unnecessary fuel consumption and emissions.

Factors Influencing the Electric Load Factor

Several factors can affect the load factor of a power system or facility:

- Operational Variability: Seasonal changes, operational hours, and process demands.
- Usage Patterns: Peak hours versus off-peak times.
- Equipment Efficiency: Modern, energy-efficient equipment can help improve load factors.
- Demand Response Initiatives: Programs that encourage shifting usage to off-peak periods.

Strategies to Improve Load Factor

Enhancing the load factor involves increasing the average load relative to the peak demand. Here are some practical strategies:

- Load Shifting: Moving energy-intensive activities to off-peak hours.
- Peak Shaving: Reducing demand during peak periods through demand response.
- Energy Conservation: Promoting efficient usage to maintain steady consumption.
- Process Optimization: Streamlining operations to reduce unnecessary peaks.

Limitations and Considerations

While the electric load factor formula provides valuable insights, it's important to recognize certain limitations:

- Variability in Data: Inaccurate or incomplete data can skew results.
- Period Selection: The choice of period (daily, monthly, yearly) affects the load factor.
- Peak Demand Measurement: Accurate recording of maximum demand is crucial.
- Contextual Interpretation: A low load factor isn't always negative; some industries inherently have fluctuating loads.

Conclusion

The electric load factor formula is a fundamental tool in energy management, serving as a benchmark for efficiency and system utilization. By calculating the ratio of average load to maximum load over a defined period, stakeholders can make informed decisions to optimize energy consumption, reduce costs, and enhance sustainability. Whether you're analyzing a manufacturing plant, a commercial building, or a power utility, understanding and applying the load factor formula is essential for effective energy planning and management.

Remember, a higher load factor generally indicates better utilization and efficiency, but context-specific factors should always be considered. Regular monitoring and strategic demand management can lead to significant operational benefits, making the electric load factor a vital metric in the pursuit of smarter energy use.

Question What is the formula for calculating the electric load factor? The electric load factor is calculated using the formula: $\text{Load Factor} = (\text{Average Load}) / (\text{Maximum Load})$ over a specific period, often expressed as a percentage. **Why is the electric load factor important in power system management?** The load factor indicates how efficiently electricity is being used over time, helping utilities optimize generation, reduce costs, and improve system reliability. **How do you compute the average load in the load factor formula?** The average load is computed by dividing the total energy consumed during a period by the total number of hours in that period. **Can the electric load factor be greater than 1?** No, the load factor cannot be greater than 1 (or 100%), as it represents the ratio of average load to peak load, which cannot exceed the maximum load. **What units are used in the electric load factor calculation?** The load factor is a dimensionless ratio, often expressed as a percentage, and can be calculated using load values in any consistent units such as kilowatts (kW) and energy in kilowatt-hours (kWh). **How can improving the electric load factor benefit utility companies?** Improving the load factor leads to better utilization of generation assets, lower operating costs, and more stable grid operations, ultimately reducing electricity costs for consumers.

Related keywords: electric load factor, load factor calculation, electricity consumption, peak load, average load, utility efficiency, power demand, energy usage, load factor formula, electrical engineering

Read the full article online: [electric load factor formula](#)